

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
27 January 2005 (27.01.2005)

PCT

(10) International Publication Number  
**WO 2005/007460 A1**

(51) International Patent Classification<sup>7</sup>: **B60R 21/01**,  
21/32

[FR/FR]; 440, rue Pasteur, F-76520 Franqueville Saint  
Pierre (FR).

(21) International Application Number:  
PCT/SE2004/001136

(74) Agent: **MEULLER, Erik**; Autoliv Development AB,  
S-447 83 Vårgårda (SE).

(22) International Filing Date: 16 July 2004 (16.07.2004)

(81) Designated States (*unless otherwise indicated, for every  
kind of national protection available*): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
0316748.3 17 July 2003 (17.07.2003) GB

(71) Applicant (*for all designated States except US*): **AUTO-  
LIV DEVELOPMENT AB** [SE/SE]; S-447 83 Vårgårda  
(SE).


(84) Designated States (*unless otherwise indicated, for every  
kind of regional protection available*): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,  
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): **NICAISE, Jean-Louis**

[Continued on next page]

(54) Title: A CRASH DETECTION SYSTEM



(57) Abstract: A crash sensor arrangement for a motor vehicle is disclosed. The crash sensor arrangement includes a first set of sensor (3, 4) comprising a respective sensor on each side of the vehicle. Each sensor (3, 4) is an accelerometer and has a predetermined sensing axis (5, 7). Each sensor (3, 4) is mounted on the vehicle (1) close to the outer skin of the vehicle and at a first longitudinal position such that the sensing axis (5, 7) of each sensor (3, 4) makes a predetermined angle to the longitudinal axis (6) of the vehicle (1). The predetermined angle is between 30° and 60°, or between -30° and -60°. The sensing axes (5, 6) are mirror symmetrical to each other relative to the longitudinal axis (6) of the vehicle (1), so that at said first longitudinal position, there are only said two respective sensors (3, 4), the sensing axes of the two sensor extending in different directions.



European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *with international search report*